



**özdöken**

**TDG-M • TDG-MT**  
**TDG-MK SERIES**  
MULTI DISC HARROW

# TDG-M

MOUNTED MULTI DISC HARROW



# TDG-MT

TRAILED MULTI DISC HARROW





STANDARD



RUBBER DISC SUSPENSION

On TDG series, each disc has individually rubber suspension.

STANDARD



CAGE ROLLER

OPTIONAL



TANDEM ROLLER



# özdöken

## TECHNICAL SPECIFICATIONS

MODEL	NUMBER OF DISCS	DISC DIMENSION	DISTANCE BETWEEN DISCS	WORKING WIDTH	TRANSPORT WIDTH	TYRE SIZE	MINIMUM WEIGHT	POWER REQUIREMENT	
	pcs	mm	cm	cm	cm		kg	hp	kW
<b>TDG-M20</b>	20	510X4 / 560X4,5	12,5	250	280	-	1350	70-90	52-67
<b>TDG-M24</b>	24	510X4 / 560X4,5	12,5	300	330	-	1550	90-120	67-90
<b>TDG-M28</b>	28	510X4 / 560X4,5	12,5	350	380	-	1750	110-140	82-105
<b>TDG-M32</b>	32	510X4 / 560X4,5	12,5	400	430	-	2060	130-160	97-120

## TECHNICAL SPECIFICATIONS

MODEL	NUMBER OF DISCS	DISC DIMENSION	DISTANCE BETWEEN DISCS	WORKING WIDTH	TRANSPORT WIDTH	TYRE SIZE	MINIMUM WEIGHT	POWER REQUIREMENT	
	pcs	mm	cm	cm	cm		kg	hp	kW
<b>TDG-MT20</b>	20	510X4 / 560X4,5	12,5	250	280	10.0/75-15.3	-	70-90	52-67
<b>TDG-MT24</b>	24	510X4 / 560X4,5	12,5	300	330	10.0/75-15.3	1700	90-120	67-90
<b>TDG-MT28</b>	28	510X4 / 560X4,5	12,5	350	380	10.0/75-15.3	2500	110-140	82-105
<b>TDG-MT32</b>	32	510X4 / 560X4,5	12,5	400	430	10.0/75-15.3	2900	130-160	97-120

## TECHNICAL SPECIFICATIONS

MODEL	NUMBER OF DISCS	DISC DIMENSION	DISTANCE BETWEEN DISCS	WORKING WIDTH	TRANSPORT WIDTH	TYRE SIZE	MINIMUM WEIGHT	POWER REQUIREMENT	
	pcs	mm	cm	cm	cm		kg	hp	kW
<b>TDG-MK36</b>	36	510X4 / 560X4,5	12,5	450	300	400/60-15.5	3600	130-150	97-112
<b>TDG-MK40</b>	40	510X4 / 560X4,5	12,5	500	300	400/60-15.5	3900	150-180	112-135
<b>TDG-MK48</b>	48	510X4 / 560X4,5	12,5	600	300	400/60-15.5	4220	180-210	135-157



[www.ozdoken.com.tr](http://www.ozdoken.com.tr) - [info@ozdoken.com.tr](mailto:info@ozdoken.com.tr)



**Tel:** +90(332) 251 67 20 (pbx) - **Faks:** +90(332) 249 09 86



1. Organize San. Bölgesi Güvençli Sokak NO:5  
**KONYA / TURKEY**